

New Product

Honey! We shrunk the VRX.

Compact, Powerful, Versatile

Introducing the all-new JBL VRX928LA Micro Line Array and matching VRX915S Subwoofer.

The VRX928LA is a lightweight (13 Kg), compact 8-inch, 2-way, 400-watt line array loudspeaker system that provides line array performance in smaller applications that do not require the long-throw characteristics of its larger, hugely successful sibling, the VRX932LA.

The VRX915S subwoofer contains a 2265G neodymium magnet, patented Differential Drive®, 15-inch woofer in a front-loaded, vented enclosure. The VRX915S complements the VRX928LA line array loudspeaker and both can be safely suspended using the VRX-SMAF small array frame.



Specifications

	NEW VRX928LA Micro Line Array	VRX932LA (The Original) MINI Line Array
LF Component	8" Differential Drive	12" Differential Drive
HF Component	2 x 1" Compression Drivers	3 x 1" Compression Drivers
Frequency Response (+/- 3dB)	87Hz – 19kHz	75Hz – 20kHz
Power	400 Watts	800 Watts
Sensitivity	90 dB Passive	95 dB Passive
Max SPL	122 dB Passive	130 dB Passive
Dispersion	100° x 15°	100° x 15°
Dimensions – HxWxD mm	230 x 420 x 270	349 x 597 x 381
Weight	12.7 Kg	21.8 Kg

	NEW VRX915S Subwoofer	VRX918S Subwoofer
LF Component	15" Differential Drive	18" Differential Drive
Frequency Response (+/- 3dB)	40Hz – 250Hz	34Hz – 220Hz
Power	800 Watts	800 Watts
Sensitivity	91 dB	95 dB
Max SPL	126 dB	130 dB
Dimensions – HxWxD mm	496 x 420 x 597	508 x 597 x 749
Weight	26.3 Kg	37 Kg

Key Features

- JBL's exclusive neodymium magnet Differential Drive® woofer for high power capacity and lightweight.
- Two patent-pending neodymium HF compression drivers.
- Constant Curvature waveguide for unprecedented array coherence
- Fly combinations of VRX928LA and Subwoofers (VRX915S) with optional array frame (VRX-SMAF)
- Integral rigging hardware for simple connection of enclosures and optional array frame. Arrays of up to six enclosures may be flown.
- Dual angle pole socket for aiming flexibility. One or two speakers may be mounted to a 35 mm pole or tripod stand.
- Array Configuration Selector permits "array shading" in passive mode.

Applications

- Music playback and sound reinforcement in small to mid-size venues.
- Entertainers, corporate A/V professionals and sound system hire companies.
- Permanent installations.

JBL VRX928LA \$3495.00 RPP
JBL VRX915S \$2795.00 RRP
JBL VRX-SMAF \$1145.00 RRP

